



SCD H™ SERIES // HIGH PERFORMANCE UV SYSTEMS

Aquafine's SCD H™ series provides TOC and chlorine destruction solutions for high volume, ultrapure, waste or reclaim applications.



MODEL SHOWN: SCD H 1350 // **INDUSTRIES:** Food & Beverage, Life Sciences, Microelectronics, Power Generation // **FLOWRATES:** 60-170 GPM @ 95% UVT, 70-200 GPM @ 99% UVT // **APPLICATIONS:** TOC, Chlorine Destruction // **DESIGN CAPABILITIES:** Modular Skid Systems

SCD H SERIES

These systems consist of 316L stainless steel treatment chamber and a UL TYPE-1 painted carbon steel control cabinet, with a maximum cable length of 15 feet (5 meters). The control cabinet features a microprocessor-based controller. The units compact size reduces footprint and maximizes installation flexibility. Aquafine's sing-ended (SE) HX lamps allows for quick change-outs without tools.

By utilizing our modular skid configurations, less floor space is consumed and higher flow rates can be treated. Aquafine's SCD H ultraviolet (UV) systems are innovative, reliable and extensively proven in ultrapure applications around the globe.

Aquafine TOC and chlorine destruction systems can be found worldwide in state-of-the-art microelectronic facilities and life science applications, where meeting stringent criteria of the cGMP and full acceptance by the FDA are mandatory.

UV Technology

Aside from being environmentally responsible, UV light technology for water treatment has several advantages. Aquafine utilizes UV light in a 185nm wavelength to effectively reduce TOC in ultrapure water applications and residual chlorine in make up water. This energy, more powerful than 254nm used in disinfection applications, promotes the formation of free radicals, leading to the oxidation of organics into CO₂ and H₂O.

Safe & Effective

UV disinfection is a chemical-free process that adds nothing to the water except UV light. It provides rapid, effective inactivation of microorganisms through a physical process. When bacteria, viruses and protozoa are exposed to the germicidal wavelengths of UV light, they are rendered incapable of reproducing and infecting. No carcinogenic disinfection by-products are created, and no transportation, storage or handling of toxic or corrosive chemicals is necessary.

Guaranteed Performance and Support Services

All of our systems come with a lifetime disinfection guarantee. Customer support is available from our Authorized Distributor Network and from our 24/7 Technical Service Group.

For questions regarding your application needs, please contact your local Authorized Distributor or Aquafine for more information.

SCD H™ SERIES // HIGH PERFORMANCE UV SYSTEMS

Model: SCD H	600 H	700 H	1000 H	1200 H	1350 H	1450 H	1550 H	1750 H						
MAXIMUM FLOW RATE														
(@ 95% UVT) GPM (M ³ /HHR)*	60 [14]	65 [15]	95 [22]	115 [26]	130 [30]	140 [32]	155 [35]	170 [39]						
(@ 99% UVT) GPM (M ³ /HHR)*	70 [16]	80 [18]	115 [26]	135 [31]	150 [34]	165 [38]	185 [42]	200 [45]						
NUMBER OF UV LAMPS (HX SINGLE-ENDED)	16	20	24	36	40	44	40	44						
ELECTRICAL REQUIREMENTS														
ELECTRICAL SUPPLY	120-240V/50-60Hz, SINGLE PHASE, 2 W + GND				208-240V/50-60Hz, SINGLE PHASE, 2 W + GND									
OPERATING POWER (NOMINAL WATTS)	2700	3250	3800	5700	6250	6800	6250	6800						
CONTROLLER/DETECTOR														
UV G400 SERIES														
LAMP STATUS INDICATOR	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD						
LAMP OUT ALERT (LOA)														
RUNNING TIME METER/CYCLE COUNTER														
HAND OFF/AUTO (HOA) 24VDC														
UV & TEMPERATURE DETECTOR														
CONTROL CABINET														
CONTROL CABINET SYSTEM RATING	C.S - UL TYPE 1, S.S. - UL TYPE 3R**				PAINTED CARBON STEEL (STAINLESS STEEL OPTIONAL)									
MATERIALS OF CONSTRUCTION														
REMOTE CABINET					OPTIONAL									
ENCLOSURE HIGH TEMP WARNING					STANDARD									
CABINET DIMENSIONS INCHES C.S. (S.S.)	22 X 30 X 16 [22 X 39 X 16]				30 X 30 X 16 [30 X 39 X 16]									
MM C.S. (S.S.)	559 X 762 X 406 [559 X 990 X 406]				787 X 787 X 406 [762 X 990 X 406]									
TREATMENT CHAMBER					316L STAINLESS STEEL									
MATERIALS OF CONSTRUCTION					Ra 32 [Ra 15 OPTIONAL]									
INTERNAL SURFACE FINISH					Water: 40° - 104° [4° - 40°] Ambient Air: 35° - 100° [2° - 38°]									
OPERATING TEMPERATURE °F / °C					150 [10]									
MAX OPERATING PRESSURE PSI (BAR)					4 / 2 or 3 (100 / 50 or 80)									
INLET/OUTLET FLANGE SIZE INCHES STANDARD/OPTIONAL (MM)	3 / 2, or 4 (80 / 50 or 100)				4 / 3 or 6 (100 / 80 or 150)									

* Dose Level: >600 mJ/cm² after 9,000 hours of operation.

** Available for stand alone units only. Skid systems available in UL TYPE-12 Painted Carbon Steel Enclosure only.



North America & International
29010 Ave Paine, Valencia, CA 91355
P +1 661 257 4770 F +1 661 257 2489
sales@aquafineuv.com | www.aquafineuv.com

Europe
Ramskamp 77-85 D-25337 Elmshorn, Germany
P +49 4121 57806 13 F +49 4121 57806 30
saleseu@aquafineuv.com | www.aquafineuv.com

Aquafine Corporation. All rights reserved. This document is not to be copied, electronically stored or reproduced without written permission from Aquafine Corporation. All specifications are subject to change without notice. For additional requirements, please contact Aquafine Corporation.



UL LISTED
Aquafine is an ISO 9001:2008 certified company.

TSG 101A-15