



TROJANUVLOGIC™ SERIES // HIGH PERFORMANCE UV SYSTEMS

A robust, highly versatile and cost effective UV water treatment system featuring proven low-pressure, high-output amalgam lamp technology.



MODEL SHOWN: TrojanUVLogic 04AS20 // **INDUSTRIES:** Aquaculture, Food & Beverage, Life Sciences, Microelectronics, Recreational Waters // **FLOWRATES:** 230-7489 GPM @ 95% UVT, 290-8141 GPM @ 99% UVT // **APPLICATIONS:** Disinfection, Chlorine/Chloramine Destruction, Ozone Destruction // **DESIGN CAPABILITIES:** Custom Configurations or Skid Capabilities

TROJANUVLOGIC SERIES

The “L-shaped” reactor design was developed using advanced computer modeling, resulting in 40% greater hydraulic efficiency than conventional systems and features the industry’s most proven low-pressure, high-output (LPHO) amalgam lamp and variable output power supply technology.

The TrojanUVLogic Series consists of a 316L stainless steel treatment chamber and a UL TYPE-3R 304L stainless steel control cabinet featuring a microprocessor-based controller. The compact size maximizes installation flexibility and preserves floor space with the ability to mount in line, horizontally or vertically.

Single-ended lamps and quartz sleeves allow for quick change-outs without tools. TrojanUVLogic systems are CE compliant as well as NSF 50 and cULus certified.

Aquafine TrojanUVLogic™ series for disinfection, ozone destruction, chlorine and chloramine reduction utilize amalgam lamp technology to meet rigid quality standards within the Aquaculture, Recreational Waters, Life Sciences and Food & Beverage industries.

Amalgam technology

Aquafine's TrojanUVLogic™ systems feature the industry's most advanced low-pressure, high-output (LPHO) amalgam lamp technology and variable output power supplies, which optimize both the dose delivered and the power consumed by the system. TrojanUVLogic systems require only one-third the number of lamps to deliver a dose equivalent to those of conventional UV systems.

Safe & Effective

UV disinfection is a chemical-free process that adds nothing to the water except UV light. It provides rapid, effective inactivation of microorganisms through a physical process. When bacteria, viruses and protozoa are exposed to the germicidal wavelengths of UV light, they are rendered incapable of reproducing and infecting. No carcinogenic disinfection by-products are created, and no transportation, storage or handling of toxic or corrosive chemicals is necessary.

Guaranteed Performance and Support Services

All of our systems come with a lifetime disinfection guarantee. Customer support is available from our Authorized Distributor Network and from our 24/7 Technical Service Group.

For questions regarding your application needs, please contact your local Authorized Distributor or Aquafine for more information.

TROJANUVLOGIC™ SERIES // HIGH PERFORMANCE UV SYSTEMS

Model: TrojanUVLogic	02AS20**	03AS20	04AS20	05AS20	06AS20	04AL20##	08AS20	06AL20	08AL20	06AL30	08AL30	12AL30	12AL40	18AL40	18AL50##	24AL50##	30AL50##	
MAXIMUM FLOW RATE																		
DISINFECTION @ 95%UVT GPM (M ³ /HR)*	230 [52]	350 [80]	480 [110]	560 [130]	695 [160]	780 [177]	875 [200]	852 ^t [194]	1014 ^t [230]	1750 [400]	2270 [516]	2765 [628]	3643 [828]	4005 [910]	6145 [1396]	8141 [1850]	7489 [1702]	
DISINFECTION @ 99% UVT GPM (M ³ /HR)*	290 [66]	430 [97]	585 [133]	690 [156]	835 [189]	935 [212]	1010 [229]	1014 ^t [230]	1040 ^s [236]	2275 [517]	2240 ^t [509]	2730 ^t [620]	3989 [906]	4750 ^{**} [1080]	7320 ^t [1664]	8141 ^s [1850]	8141 ^{t+} [1850]	
OZONE DEST. @ 99% UVT GPM (M ³ /HR)†	100 [23]	145 [32]	195 [44]	145 [53]	235 [63]	280 [72]	320 [78]	345 [78]	450 [102]	546 [124]	760 [173]	990 [225]	1240 [282]	1772 [403]	2589 [588]	3253 [739]	4292 [975]	5265 [1196]
NUMBER OF UV LAMPS (LP)	2	3	4	3	6	4	8	6	8	6	8	12	18	18	24	30		
ELECTRICAL REQUIREMENTS																		
ELECTRICAL SUPPLY	208-240VAC 50Hz SINGLE PHASE & 60Hz SINGLE PHASE 2+ GND																	
OPERATING POWER (NOMINAL WATTS)	346	534	692	849	1007	1113	1323	1639	2170	1639	2170	3218	4750	6310	7870			
CONTROLLER																		
UV SENSOR W/ 4-20mA	STANDARD																	
LAMP STATUS INDICATOR	STANDARD																	
LAMP OUT ALERT DRY CONTACT	STANDARD																	
TEMP. SWITCH	STANDARD																	
RUNNING TIME INDICATOR	STANDARD																	
REMOTE ON/OFF 24-240V AC/DC	STANDARD																	
CONTROL CABINET (CC)																		
CC SYSTEM RATING	NEMA 12																	
MATERIALS OF CONSTRUCTION	304 STAINLESS STEEL (PAINTED CARBON STEEL OPTIONAL)																	
CC DIMENSIONS - HXWXD INCHES (CONTACT AQUAFINE FOR CE)	24 X 24 X 10	24 X 30 X 10	24 X 24 X 10	24 X 30 X 10	24 X 24 X 10	24 X 30 X 10	24 X 24 X 10	24 X 30 X 10	24 X 30 X 10	24 X 30 X 10	24 X 30 X 10	24 X 30 X 10	48 X 36 X 10					
TREATMENT CHAMBER																		
MATERIALS OF CONSTRUCTION	316L STAINLESS STEEL																	
INTERNAL SURFACE FINISH	Ra 32 [Ra 15 OPTIONAL]																	
OPERATING TEMPERATURE °F (°C)	Water: 41° - 104° [5° - 40°] Ambient Air: 34° - 104° [1° - 40°]																	
MAX OPERATING PRESSURE PSI (BAR)	150 [10]																	
INLET/OUTLET FLANGE INCHES (MM)	4 [100]	MANUAL	MANUAL OR AUTOMATIC	6 [150]	MANUAL	MANUAL OR AUTOMATIC	10 [250]	10 [250]	10 [250]	14 [350]	14 [350]	14 [350]	14 [350]	18 [450]				
Dose Levels: * 30 mJ/cm ² after 12,000 hours of operation. + 90 mJ/cm ² after 12,000 hours of operation.																		
‡ 40 mJ/cm ² after 12,000 hours of operation.																		
§ 47 mJ/cm ² after 12,000 hours of operation.																		
** 49 mJ/cm ² after 12,000 hours of operation.																		
† 58 mJ/cm ² after 12,000 hours of operation.																		
All These models are not NSF certified. For more information, contact Aquafine.																		



Aquafine is an ISO 9001 certified company.



A TROJAN TECHNOLOGIES BUSINESS

North America & International
29010 Ave Paine, Valencia, CA 91355
P +1 661 257 4700 F +1 661 257 2489
www.aquafine.com

Europe
Rantskamp 77-95 D-25337 Elmshorn, Germany
P +49 4121 578016 13 F +49 4121 57806 30
www.aquafine.eu

© Aquafine Corporation 2019. All rights reserved. This document is not to be copied, electronically stored or reproduced without written permission from Aquafine Corporation. All specifications are subject to change without notice. For additional requirements, please contact Aquafine Corporation.

TSG 178A-15