

CABLES FOR A MOVING WORLD



**TRATOS
FIRESAFE TW100®**

Jan 2011



TRATOS FIRESAFE TW100®

ZERO HALOGEN, LOW SMOKE CABLES having enhanced circuit integrity when exposed to fire

TRATOS FIRESAFE TW100® - 600/1000V

FEATURES AND PERFORMANCES



CONSTRUCTION

- **Conductor:** Stranded plain annealed copper wire conductor
- **Insulation:** Mica-glass fire resistant tape covered by an extruded layer of cross-linked Zero Halogen, Low Smoke (OHLS®) insulating compound

STANDARDS

- BS 6387 categories C, W & Z (when applied to a single cable)
- IEC 60331 Exceeds IEC 60331 - 3 hours at 750°C - when the test temperature was increased to 950°C, equivalent to BS Category C. (This test was also satisfactorily applied to Sifer cable in an earthed metal conduit, as per LPCB guidance notes)
- 6387
- IEC 60332-1, BS EN 50265, IEC 60332-3, BS EN 50266 (Flame propagation)
- IEC 60754-1, BS EN 50267-2-1 (Acid gas emission)
- IEC 61034, BS EN 50268 (Smoke emission)



Characteristics:

Working temperature	-40°C to +90°C (The cable should not be flexed when either the ambient or cable temperature is below 0°C)
Min. bending radius	8 x overall diameter of cable
Voltage rating (Uo/U)	600/1000V

A full range of insulation colours is available including green/yellow.
Sheathed versions also available. Details available upon request.

TRATOS FIRESAFE TW100 - 600/1000V

Cross Section	Insulation Thickness	Conductor DC Resistance at 20 °C Max	Maximum Temperature of the Conductor During Operation	Nominal Diameter	Nominal Cable Weight
mm ²	mm	Ω/Km	°C	mm	Kg/km
1,5	1,0	12,10	90	3,9	32
2,5	1,0	7,41	90	4,6	43
4	1,0	4,61	90	5,1	55
6	1,0	3,08	90	5,6	85
10	1,0	1,83	90	6,8	146
16	1,0	1,15	90	7,8	198
25	1,2	0,727	90	9,2	320
35	1,2	0,524	90	10,2	410
50	1,4	0,387	90	12,0	549
70	1,4	0,268	90	14,2	770
95	1,6	0,193	90	15,6	1140
120	1,6	0,153	90	17,5	1425
150	1,8	0,124	90	19,4	1720
185	2,0	0,091	90	22,5	2155
240	2,2	0,074	90	24,2	2900
300	2,4	0,061	90	28,0	3540
400	2,6	0,047	90	31,0	4410
500	2,8	0,036	90	34,8	5660
630	2,8	0,028	90	37,8	7140



Tratos Cavi Spa

Via Stadio, 2
52036 – Pieve Santo Stefano
Arezzo - ITALY
Tel: +39-0575-7941
Fax: +39-0575-794246
e-mail: info@tratos.it

Tratos Ltd - United Kingdom

Park Road . Holmewood Industrial Park
Holmewood . Chesterfield . S42 5UW
United Kingdom
Tel: 01246 858000 - Fax: 01246 858001
e-mail: info@tratos.co.uk
web: www.tratos.co.uk

Tratos Ltd - Germany

Alter Bentheimer Weg 4
48465 Schüttorf - Germany
Tel: 0049-5923-96 99 66
Fax: 0049-5923-96 99 67
e-mail: info@tratoscavi.de

Tratos Cavi Iberica S.L

Bloque 6, 1ºD. - Alcobendas
28109 Madrid - Spain
Tel: + 34 9162 55887
e-mail: info@tratos.com.es

Tratos Cavi SpA - China Office

Unit 3, No.879, Shenfu Road
Xinzhuang Industrial Zone
Shanghai, China (201108)
e-mail info.china@tratos.it